



Note:

- ①. TCP/IP Intelligent System - Sub-monitoring and Control/Hot-swappable
- ②. C13 Lockable with LED Indicator × 6 + C39 Lockable with LED Indicator × 2 - Group A
- ③. C13 Lockable with LED Indicator × 6 + C39 Lockable with LED Indicator × 2 - Group B
- ④. 2P 20A Hydraulic Magnetic Circuit Breaker × 2 - A + B
- ⑤. IO Sensor Interface Board - T/H × 3 + SMOKE × 1 + DOOR × 2 + WATER + INPUT

Note : Laser Marking | Serial Number Marking

No.	Main Items	Basic Description					
1	Electrical Parameters	Rated Voltage:	250V AC	Rated Current:	30A	Maximum Power:	7500W
2	Enclosure	Material:	Aluminum Alloy	Type :	SY-610 SY-611	Color:	Black
3	Incoming line and installation	Incoming line direction:	Top incoming line	Cable Locking:	PG19	Wiring Method:	L6-30R
4	Internal Connection	Main 6mm ² ZR-Rv wire + 6mm ² copper bar connection					
5	Accessories	M6×12 cross bolts and nuts 4 sets Installation Manual					

宁波盛邦通信设备有限公司 Ningbo DCDU Power Distribution Equipment Co.,Ltd			
Product Name		SmartPDU	
Customer No.			
Model No.		Z247.5016.DP01.102	
Drawing No.		2025022801	
Design	Alan-Wang	Check	Kang
Verify	Kang	Approve	Huang
Date	2025.02.28		
Tolerance ±2			